

MODEL C 1012/2S

CHRISTIE
AUTOMOTIVE PRODUCTS

BATTERY SERVICE EQUIPMENT

DUAL 10 AMP CONSTANT CURRENT SMALL BATTERY CHARGER

Recover batteries with partial sulfation due to seasonal use or discharge during long storage periods. Electronic controls automatically adjust charging voltage (up to 22 volts) during de-sulfation mode.

Designed for small lead-acid and gel cell batteries, the C1012/2S charges two batteries simultaneously and independently at 12 volts. Simply connect, set charger rate (0-10 amps) and set timer control (0-2 hrs).

- **Dual Outputs:**

Two chargers in one box. Two independent control boards make each charger unaffected by the other. Two sets of controls; two sets of output cables.

- **Solid State Circuitry**

Control circuits provide constant current charging controls for maximum charging performance. Recover sulfated batteries with automatic recovery mode which provides higher charging voltage (up to 22 volts) to break down sulfation due to deep discharge.

- **Positive Polarity Protection**

Automatic Positive Polarity Protection prevents the risk of accidents or explosions due to sparks in the case of reverse connections.



Electrical Specs:

AC Input Power:

120 Volts AC
2 amps AC 60Hz

DC Output Power:

12 Volts DC
10 amp DC

Dimensions:

Height 7.5 in.
Depth 9.5 in.
Width 14.5 in.
Shipping Wt: 32 lbs.

MADE IN USA

©Copyright Christie Automotive

CHRISTIE.
AUTOMOTIVE PRODUCTS

PROFESSIONAL DUTY BATTERY SERVICE EQUIPMENT

2851 McGaw Avenue, Irvine, CA 92614
800.365.1003 FAX 949.553.2003
www.ChristieAutomotive.com